

See on ActionScript-i programm on Frame 1-l.

```
// Uue CSS faili loomine ja laadimine
LoadVars objeksi külge
var myVars:LoadVars = new LoadVars();
var styles = new TextField.StyleSheet();
var txt_url = "tekstid.txt";
var css_url = "html_styles.css";
// Laadida tekst
myVars.load(txt_url);
myVars.onData = function(content) {
    storyText = content;
};
// Laadida CSS
styles.load(css_url);
styles.onLoad = function()
{
    tekst.styleSheet = styles;
    tekst.text = storyText;
};
```

See on faili tekstid.txt sisu

```
<p class='pealkiri'>HTML-i ja CSS-i
kasutamine Flash-is</p><p><br><span
```

```
class='sisu'>HTML-i vorminduses teksti
v&#245;ib lugeda eraldi failist
tekstiv&#228;lja<br><a
href='http://www.tpt.edu.ee'
target='_self'>Tallinna
Pul&#252;tehnikum</a></p>
```

See on html_styles.css sisu

```
p {
    color: #008000;
    font-family: Arial;
    font-size: 14pt;
    display: inline; font-weight:bold
}

a:link {
    color: #FF0000;
}
a:hover{
    text-decoration: underline;
}

.pealkiri {
    color: #331133;
    font-family: Arial;
    font-size: 20px;
    font-weight: bold;
    display: block
}
```